

DECLARATION OF PERFORMANCE

DoP ref. SST1306044



Name of manufacturer	Teco Building Products Wellington Road, Portslade, Brighton, BN41 1DN
Product type	Teco St/St Screw in Starter Tie c/w plug
Intended use	Horizontal asymmetrical cavity wall tie for connecting new masonry walls to existing masonry walls
System of AVCP	3
Harmonised standard	EN 845-1:2003+A1:2008

Teco is an ISO9001 registered firm audited by QMS International plc.
Structural Consultants C4Ci Ltd.
Factory Production Control assessed and audited by BM TRADA CE Scheme for Construction Products Notified Body No.1224
Where appropriate, tested by CERAM Research Ltd Notification Body No.1289

Product Code

- SST180
- SST200
- SST225
- SST275

- Maximum Cavity 100mm**
- Minimum Embedment: 62.5mm**
- Minimum Mortar Joint: 10mm**



Declared Performance		
<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
Compressive Load Capacity	2260N	EN845-1:2003+A1:2008
Tensile Load Capacity	2076N (Mortar End) 2050N (Threaded End)	
Displacement at 1/3 load capacity	No performance declared	
Durability	Material / Coating reference 3 acc. to EN 845-1 Table A.1	
Water Shedding Capacity	Resistant	
Dangerous substances	Meets UK Building Regulation requirements	

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Rhonda Backwell
Director

01/07/2013 Brighton